Product Features

FEATURES

- Programmable microstepping drive with advanced current control
- Q Programmer[™] for robust motion control programming
- 744 lines of stored program capability
- Math calculations using analog and digital parameters
- Supports all "S" drive control modes as well
- Modbus/RTU for easy PLC and HMI communication
- Compatible with many 3rd party HMIs
- Wide current range 0.1 to 5.0 A/phase (peak of sine) with idle current reduction
- Advanced anti-resonance algorithm
- Torque ripple smoothing
- 8 digital inputs, 4 digital outputs, optically isolated
- 2 analog inputs, +/-10 volt range
- RS-232 cable and mating connectors included



DESCRIPTION

The ST5-Q-NN stepper drive is a DC-powered microstepping drive for controlling two-phase, bipolar step motors. It offers advanced current control and a sophisticated 3rd generation anti-resonance algorithm that electronically dampens motor and system resonances to improve motor smoothness and usable torque over a wide speed range. The drive also employs electronic torque ripple smoothing and microstep emulation to greatly reduce motor noise and vibration. The drive must be powered from 24-48 VDC and can output up to 5.0 A/phase (peak-of-sine) to the step motor. Over-voltage, over-temperature and over-current protection features prevent damage while running in adverse conditions. The drive is complemented by a specifically matched set of NEMA 11 through NEMA 23 frame stepper motors (see Related and Recommended products below).

The ST5-Q-NN can operate in all of the same control modes as the S model (pulse & direction, velocity, streaming commands, SiNet Hub operation), plus it has the ability to run stand-alone Q programs stored in non-volatile memory. Q programs are created using the Q ProgrammerTM software, which provides multi-tasking, math functions, conditional processing, data register manipulation, and more features in a robust yet simple text-based programming language. The drive is setup and configured using Applied Motion's ST ConfiguratorTM software. Preconfigured motor setup files included with ST ConfiguratorTM make it easy to set up the drive for optimum results.

For connecting to external devices such as control signals, incremental encoders, limit switches, proximity or photoelectric sensors, PLC I/O, lamps, and other devices, the drive comes with 8 digital inputs, 4 digital outputs, and 2 single-ended analog inputs (analog inputs can be wired together as 1 differential analog input). Adjustable digital filters are present on the digital inputs for enhanced reliability in noisy environments.

The drive comes with an RS-232 port for configuration, serial communications and programming.

All ST drives are CE approved and RoHS compliant.


SPECIFICATIONS	SPECIFICATIONS					
Model Number	ST5-Q-NN					
Part Number	5000-128					
Supply Voltage	24-48 VDC					
Supply Voltage Type	DC					
Control Modes	 Step & Direction Velocity (Oscillator) Streaming Commands Analog Positioning Encoder Following Q Programming SiNet Hub Compatible Modbus 					
Output Current	1110 010 010					
Output Current Communication Ports	0.1-5.0 A/Phase RS-232					
Encoder Feedback	No					
Step Resolution	· Full					
	HalfMicrosteppingMicrostep Emulation					
Idle Current Reduction	0-90%					
Setup Method	Software setup					
Digital Inputs	8					
Digital Outputs	4					
Analog Inputs	1 differential or 2 single-ended					
Dimensions	5.0 x 3.0 x 1.75 inches					
Weight	10.4 oz					
Operating Temperature Range	0-70 °C					
Ambient Temperature Range	0-55 °C					
Ambient Humidity	90% max, non-condensing					
Status LEDs	1 red, 1 green					
Circuit Protection	Short circuitOver-voltageUnder-voltageOver-temp					

DOWNLOADS & SOFTWARE			
Manuals	ST5 10-Q QuickSetup 920-0007E.pdf Host Command Reference Rev I.pdf ST5-10-QSi Hardware Manual 920-0004F.pdf ModbusManual 920-0072.pdf		
Datasheet	ST Datasheet 925-0007.pdf		
2D Drawing	ST5 10 Dimensions.pdf ST T simple 3D.pdf		
3D Drawing	ST5 10-Q Si C SIMPLE.igs		
Speed-Torque Curves	ST speed-torque.pdf		
Agency Approvals	ST-Q-Si-C-IP CE DOC.pdf		
Application Notes	APPN0021 5V-Keepalive-Circuit.pdf APPN0019 Analog-positioning-using-Q-program.zip APPN0018_EZ-Series-Touchpanel-HMI.zip APPN0016_Simple-25-pin-mating-connections.pdf APPN0015_Make-a-serial-programming-cable.pdf		
Software Downloads	SCL Utility ST Configurator™		
Sample Code	scldemo.zip		

All Downloads and Software can be downloaded from TWHC website

2D DRAWING

Mechanical Outline



PRODUCTS IN THE SERIES MODBUS PRODUCTS

MODEL NUMBER	SUPPLY VOLTAGE	CONTROL MODES	OUTPUT CURRENT	COMMUNICATION PORTS
ST5-Q-NN	24-48 VDC	Step & Direction Velocity (Oscillator) Streaming Commands Analog Positioning Encoder Following Q Programming SiNet Hub Compatible Modbus	0.1-5.0 A/Phase	RS-232
ST5-Q-NN	24-48 VDC	Step & Direction Velocity (Oscillator) Streaming Commands Analog Positioning Encoder Following Q Programming Modbus	0.1-5.0 A/Phase	RS-232 RS-485

PRODUCTS IN THE SERIES ST STEPPER DRIVES

MODEL NUMBER	SUPPLY VOLTAGE	CONTROL MODES	OUTPUT CURRENT	COMMUNICATION PORTS
ST5-Q-NN	24-48 VDC	Step & Direction Velocity (Oscillator) Streaming Commands Analog Positioning Encoder Following Q Programming SiNet Hub Compatible Modbus	0.1-5.0 A/Phase	RS-232